

Trade name: Spare cartridge 110ml for GasBuddex

Version: 2 / DK Date revised: 31.03.2025

Substance number:: 1756 Replaces Version: 1 / DK Print date: 03.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Spare cartridge 110ml for GasBuddex

Registration no.

UFI USU4-X0T4-V003-D21M

Substance / product identification

PR-No. 1730, 1731, 1756, 1766

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Liquefied gas mixture

1.3. Details of the supplier of the safety data sheet

Address/Manufacturer

Albert Kerbl GmbH

Felizenzell 9

84428 Buchbach

Telephone no. +49 8086 933-100 Fax no. +49 8086 933-500

Information provided Albert Kerbl GmbH Tel.: 0049-(0)8086-933-302

by / telephone

E-mail address of

sdb-team@kerbl.com

person responsible

for this SDS

1.4. Emergency telephone number

Joint poison information center for the states of Mecklenburg-Western Pomerania, Saxony, Saxony-Anhalt and Thuringia c/o HELIOS Klinikum Erfurt Nordhäuser Strasse 74

Tel.: (03 61) 73 07 30 - Fax: (03 61) 7 30 73 17

E-Mail: ggiz@ggiz-erfurt.de - Internet: www.ggiz-erfurt.de

Nødtelefon: +45 82 12 12 (Giftlinjen, Bispebjerg Hospital)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Gas 1 H220 H280 Press. Gas (Liq.)

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008

For explanation of abbreviations see section 16.

2.2. Label elements

Page: 1 (11)

Trade name: Spare cartridge 110ml for GasBuddex

Version: 2 / DK Date revised: 31.03.2025

Substance number:: 1756 Replaces Version: 1 / DK Print date: 03.04.2025

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.
P410+P403 Protect from sunlight. Store in a well-ventilated place.

2.3. Other hazards

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms. The product contains no vPvB substances. The product contains no PBT substances

The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 3: Composition/information on ingredients

Further ingredients

Butane

CAS No. 106-97-8 EINECS no. 203-448-7

Concentration >= 50 %

Advice: [3]

Classification (Regulation (EC) No. 1272/2008)

Flam. Gas 1 H220 Press. Gas (Liq.) H280

Additional remarks:

CLP Regulation (EC) No 1272/2008, Annex VI, Note C, U

Isobutane

CAS No. 75-28-5 EINECS no. 200-857-2

Concentration >= 10 < 25 %

Advice: [3]

Classification (Regulation (EC) No. 1272/2008)

Flam. Gas 1 H220



Trade name: Spare cartridge 110ml for GasBuddex

Version: 2 / DK Date revised: 31.03.2025

Substance number:: 1756 Replaces Version: 1 / DK Print date: 03.04.2025

Press. Gas (Liq.) H280

Additional remarks:

CLP Regulation (EC) No 1272/2008, Annex VI, Note C, U

propane

CAS No. 74-98-6 EINECS no. 200-827-9

Concentration >= 10 < 25 %

Advice: [3]

Classification (Regulation (EC) No. 1272/2008)

Flam. Gas 1 H220 Press. Gas (Lig.) H280

Additional remarks:

CLP Regulation (EC) No 1272/2008, Annex VI, Note U

Note

[3] Substance with occupational exposure limits

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take affected person to fresh air.

After inhalation

In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination. In high concentrations may cause asphyxiation. Symptoms mayinclude loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

After skin contact

In case of frostbite, rinse with plenty of water. Do not remove clothing. Cover wounds with sterile dressing. Summon a doctor immediately.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). Seek medical advice immediately.

After ingestion

Ingestion is not considered a potential route of exposure.

Adhere to personal protective measures when giving first aid

First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / hazards

No further relevant information available.

SECTION 5: Firefighting measures

Trade name: Spare cartridge 110ml for GasBuddex

Version: 2 / DK Date revised: 31.03.2025

Substance number:: 1756 Replaces Version: 1 / DK Print date: 03.04.2025

5.1. Extinguishing media

Suitable extinguishing media

Dry powder, Carbon dioxide, Sand

Non suitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

If a fire breaks out nearby, pressure build-up and danger of bursting are possible. In the event of fire the following can be released: Carbon monoxide (CO)

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Do not inhale explosion and/or combustion gases. Use self-contained breathing apparatus. Wear protective clothing.

Other information

Cool endangered containers with water spray jet. If possible, stop flow of product. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosivereignition may occur.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear self-contained breathing apparatus when entering the area unless the atmosphere is proven to be non-hazardous. Clear area. Ensure adequate ventilation. Keep away sources of ignition. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Try to stop the gas leakage. Prevent penetration into sewers, cellars, working pits or other places where accumulation can be dangerous.

6.3. Methods and material for containment and cleaning up

Ensure sufficient ventilation. Keep area evacuated and free from ignition sources until all spillage has evaporated. (Ground is free of frost).

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Reliably ground equipment. Only use equipment that is suitable for this product and the intended pressure and temperature. Follow the instructions for use exactly. Keep away from sources of ignition!

Advice on protection against fire and explosion

Keep away from sources of heat and ignition. No smoking. Take action to prevent static discharges. Avoid impact and friction. Use only explosion-proof equipment. Keep away from combustible material. Wear shoes with conductive soles.

7.2. Conditions for safe storage, including any incompatibilities

Recommended storage temperature



Trade name: Spare cartridge 110ml for GasBuddex

Version: 2 / DK Date revised: 31.03.2025

Substance number:: 1756 Replaces Version: 1 / DK Print date: 03.04.2025

Value < 50 °C

Requirements for storage rooms and vessels

The official regulations for the storage of pressurised gas packages must be observed. Storage rooms must be properly ventilated. Store away from oxidising gases and other oxidising substances.

Hints on storage assembly

Do not store with strong oxidizing agents.

Storage classes

Storage class according to TRGS 510 2A Gases

Further information on storage conditions

Keep container tightly closed. Keep container in a well-ventilated place. Keep in a cool place

7.3. Specific end use(s)

Liquefied gas mixture

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Other information

There are not known any further control parameters.

8.2. Exposure controls

General protective and hygiene measures

Do not smoke during work time. Do not inhale gases/vapours/aerosols. Do not eat or drink during work time. Storage of foodstuffs in work rooms is forbidden. Wash hands before breaks and after work.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Filter apparatus, filter A/P3

Hand protection

Protective gloves

Use chemical-resitant gloves! Suitable for short-term use: 1,4mm Latex or 0,85mm Nitrile

(Recommended: Kerbl Fletex (Latex), or Kerbl Chemex (Nitrile))

Hand protection must comply with EN 374.

Protect skin from splashes of liquid.

Eye protection

Avoid contact with eyes. Safety glasses with side protection shield; Eye protection must comply with EN 166. Face shield

Body protection

Clothing as usual in the chemical industry. Fire-resistant antistatic protective clothing

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Pressurised liquified gas

ColourcolourlessOdourodourless

Melting point

Remarks not determined

Page: 5 (11)

Trade name: Spare cartridge 110ml for GasBuddex

Version: 2 / DK Date revised: 31.03.2025

Substance number:: 1756 Replaces Version: 1 / DK Print date: 03.04.2025

Freezing point

Remarks not determined

Boiling point or initial boiling point and boiling range

Value -0,5 °C Remarks Information refers to the main component.

Flammability

Flammable.

Upper and lower explosive limits

Lower explosion limit 1,4 %(V)
Upper explosion limit 9,4 %(V)
Remarks Information refers to the main component.

Flash point

Value -60 °C Remarks Information refers to the main component.

Auto-ignition temperature

Value 365 °C Remarks Information refers to the main component.

Decomposition temperature

Remarks not determined

pH value

Remarks not determined

Viscosity

Remarks not determined

Solubility(ies)

Remarks not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

Vapour pressure

Value 2,73 bar

Density and/or relative density

Value 0,559

Relative vapour density

Value 1,91

9.2. Other information

Odour threshold

Remarks not determined

Evaporation rate (ether = 1):

Remarks not determined

Solubility in water

Remarks No data available



Trade name: Spare cartridge 110ml for GasBuddex

Version: 2 / DK Date revised: 31.03.2025

Substance number:: 1756 Replaces Version: 1 / DK Print date: 03.04.2025

Explosive properties

evaluation Container is under pressure: may burst when heated.

Oxidising properties

Remarks not determined

Other information

Gas / vapours are heavier than air. Can accumulate in enclosed spaces especially at or below ground

level.

SECTION 10: Stability and reactivity

10.1. Reactivity

Container is under pressure: may burst when heated.

10.2. Chemical stability

No decomposition if used as prescribed.

10.3. Possibility of hazardous reactions

No dangerous reactions when stored and handled according to instructions. Vapours can form an explosive mixture with air. May react violently with oxidising substances.

10.4. Conditions to avoid

Sun exposure, high temperatures, ignition sources.

10.5. Incompatible materials

Reacts violently with: Strong oxidising agents

10.6. Hazardous decomposition products

Hazardous decomposition products should not be formed under normal storage and use conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

Acute inhalational toxicity

Remarks Based on available data, the classification criteria are not met.

Acute inhalative toxicity (Components)

Butane

Species mouse

LC50 1237 mg/l

propane

Species mouse

LC50 1237 mg/l

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Trade name: Spare cartridge 110ml for GasBuddex

Version: 2 / DK Date revised: 31.03.2025

Substance number:: 1756 Replaces Version: 1 / DK Print date: 03.04.2025

Serious eye damage/irritation

Remarks Based on available data, the classification criteria are not met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

Subacute, subchronic, chronic toxicity

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

Remarks Based on available data, the classification criteria are not met.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

Other information

In low concentrations may cause narcotic effects.

Symptoms may include dizziness, headache, nausea and loss of co-ordination. In high concentrations may cause asphyxiation.

SECTION 12: Ecological information

12.1. Toxicity

General information

The product is not expected to be hazardous to the environment.

Fish toxicity (Components)

Butane

Species Fish

LC50 24,11 to 147,54 mg/l

Algae toxicity (Components)

Butane

Species Algae

EC50 7,71 to 16,5 mg/l

12.2. Persistence and degradability



Trade name: Spare cartridge 110ml for GasBuddex

Version: 2 / DK Date revised: 31.03.2025

Substance number:: 1756 Replaces Version: 1 / DK Print date: 03.04.2025

General information

not determined

Biodegradability (Components)

Butane

Value 100 %

Duration of test 385,5 h

Method Biodegradation test, predates, OECD test

Isobutane

Value 100 %

Duration of test 385,5 h

Method Biodegradation test, predates, OECD test

propane

Value 100 %

Duration of test 385,5 h

Method Biodegradation test, predates, OECD test

12.3. Bioaccumulative potential

General information

not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

12.4. Mobility in soil

General information

not determined

12.5. Results of PBT and vPvB assessment

General information

Mixture does not meet PBT or vPvB criteria.

Results of PBT and vPvB assessment

The product contains no PBT substances

The product contains no vPvB substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties with respect to the envrionment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

General information

not determined

General information / ecology

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

Trade name: Spare cartridge 110ml for GasBuddex

Version: 2 / DK Date revised: 31.03.2025

Substance number:: 1756 Replaces Version: 1 / DK Print date: 03.04.2025

13.1. Waste treatment methods

Disposal recommendations for the product

EWC waste code 16 05 04* gases in pressure containers (including halons) containing

dangerous substances

The listed waste code numbers, according to the European Waste Catalogue (EWC), are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Vapours can form an explosive mixture with air.

Waste gasshould be flared through a suitable burner with flash back arrestor. Do not discharge into any placewhere its accumulation could be dangerous. Contact supplier if guidance is required.

Disposal recommendations for packaging

Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number or ID number	2037	2037	2037
14.2. UN proper shipping name	RECEPTACLES, SMALL, CONTAINING GAS (GAS CARTRIDGES)	RECEPTACLES, SMALL, CONTAINING GAS (GAS CARTRIDGES)	RECEPTACLES, SMALL, CONTAINING GAS (GAS CARTRIDGES)
14.3. Transport hazard class(es)	2	2.2	2.2
Label	2	2	2
Limited Quantity	11	11	
Transport category	3		
Tunnel restriction code	E		

Information for all modes of transport

14.6. Special precautions for user

none

Other information

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Other transport information:

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the eventof an accident or an emergency.

Before transporting product containers ensure that they are firmly secured. Ensure that the container valve



Trade name: Spare cartridge 110ml for GasBuddex

Version: 2 / DK Date revised: 31.03.2025

Substance number:: 1756 Replaces Version: 1 / DK Print date: 03.04.2025

is closed and not leaking

Ensure that the valve outlet capnut or plug (where provided) is correctly fitted. Ensure that the valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

Remark: Both cartridges in the box are without a releasedevice.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

VOC (CH) 100 %

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

CLP categories listed in Chapter 3

Flam. Gas 1 Flammable gas, Category 1

Press. Gas (Liq.) Gases under pressure (liquefied gas)

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***
This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.
Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Page: 11 (11)